

3d Brain Atlas Reconstructor on-line service

getAvailableDatasets

Return an AJAX data describing CAF datasets (atlases) available to the user in the service.

syntax

```
getAvailableDatasets
```

AJAX data type

```
{
  String: [String,
            String,
            String,
            String,
            {
              String: Boolean,
              ...
            },
            String],
  ...
}
```

AJAX data description

The data is provided in format:

```
{
  <id>: [<name>,
            <root>,
            <description>,
            <date>,
            {
              "cafslides": <cafslides>,
              "reconstructions": <reconstructions>,
              "thumbnails": <thumbnails>,
              "customreconstruction": <customreconstruction>,
              "hidden": <hidden>,
              "internal": <internal>,
              "enabled": true
            },
            <unit>],
  ...
}
```

where:

<id>
is the atlas identifier in the service,
<name>
is the atlas name,
<root>

is the name of the root element in the atlas structures hierarchy tree,
<description>
 is the atlas description,
<date>
 is the CAF dataset compilation date,
<cafslides>
 indicates if CAF slides are available,
<reconstructions>
 indicates if reconstructions of structures in the atlas are available,
<thumbnails>
 indicates if thumbnail images of structures in the atlas are available,
<customreconstruction>
 indicates if it is possible to submit custom reconstruction of structures in the atlas,
<hidden>
 indicates if the dataset is invisible in the front-end interface,
<internal>
 indicates if access to the dataset is restricted to limited group of users,
<unit>
 is the spacial reference system unit used in the dataset.

Example

- <http://service.3dbar.org/getAvailableDatasets>